

ProArmor™ Synthetic Roof Underlayment



ProArmor™ Synthetic Roof Underlayment



Owens Corning® ProArmor™ Synthetic Roof Underlayment with Fusion Back Coating Technology is strong, durable and repels water unlike #15 felt. It's also light, easy to install and contributes to safe working conditions.

Rating: Not Rated Yet
[Ask a question about this product](#)

Manufacturer [Owens Corning](#)

Description

- Dual-surface slip resistance: **Fusion Back Coating Technology** paired with an industrial non-woven surface provides excellent walking conditions during shingle application even on steeply pitched roofs
- Repels moisture and helps provide protection against water infiltration
- Resists stretching and tearing around fasteners
- Available in 42-inch lightweight rolls for easy installation
- 10-Year Limited Warranty*
- For use under asphalt shingles only

ProArmor™ Synthetic Roof Underlayment is part of the Owens Corning® [Total Protection Roofing System](#)™§.

[Product Specifications](#) [Technical Documents](#) [Applicable Standards](#)

Roll Length	286 ft.
Roll Width	42 in.
Nominal Weight per Roll**	25 lb.
Coverage (with 3-in. overlap)	929 sq. ft.
Exposed Color	Light gray
Surface Construction	Industrial Nonwoven

* See actual warranty for complete details, limitations and requirements. A longer limited warranty term applies when ProArmor™ is used in conjunction with Owens Corning® Roofing Shingles.

Accessories: ProArmor™ Synthetic Roof Underlayment

§ Excludes non-Owens Corning® roofing products such as flashing, fasteners and wood decking.

** Includes core weight.

International Code Council Evaluation Services Report.

*** Underlayment is tested as part of a roof assembly that includes wood decking, underlayment and asphalt shingles.

² Applies to all areas that recognize Miami-Dade Product Control Section.